

# TECHNICAL DATA SHEET



## Movement bead PVC Article no. 3340 - 3344

### Specifications:

Basic shape	L-profile				
	Article No.	3340	3341	3342	3343
Plaster thickness	4 mm	6 mm	10 mm	15 mm	20 mm
Bar lengths	2,5 m	2,5 m	2,5 m	2,5 m	2,5 m
Packing unit	10 Stück	10 Stück	10 Stück	10 Stück	10 Stück
Packing content	25 m	25 m	25 m	25 m	25 m

### Application: interior and exterior plastering

Movement bead for different plaster thicknesses in the interior and exterior.  
To set up vertically movement joint connections.  
These profiles could be used at an even wall area.

### Equipment of the product:

The movement beads 3340 – 3343 consist of two punched Co-extruded profile out of impact resistant and UV- and weather-proof PVC with a soft waist.  
The movement bead 3344 consist of two punched profiles out of impact resistant and UV- and weather-proof PVC witch are connected by a coextruded profile out of white rigid-PVC and soft PVC.  
The soft waist out of soft PVC is protected by a peel-off film against vitiations while mounting.

### Important details:

Dry storage!  
Horizontal transporting and stocking at even rest!  
Possible section butts must be sealed separately!

All details complies the up-to date our knowledge and experience. Our information characterise simply the character our products and don't account for contractual legal relationship. They don't absolve the customer from verifying our products to their applicability for the contemplated usage on their own. We reserve the right for changing due to technical or planning laws. Product-drawings on this sheet aren't true to scale. With publishing this technical data sheet are all back issues invalid. As of 05.2010